

Spray gel composition with Eastman AQ™ 48 ultra polymer

Shear-thinning, spray gel composition

This spray gel composition demonstrates the use of Eastman AQ™ 48 polymer as a film-former and hair fixative with Laponite™ XLG silicate to make a translucent gel. The gel holds air bubbles upon standing, but is extremely shear-thinning, providing excellent spray-out from a standard pump-spray container.

Part A	wt %
Deionized or tap water	60.2
Laponite™ XLG Sodium Magnesium Silicate ¹	2.8
Part B	
Water	29.4
Glycerin	3.0
Eastman AQ™ 48 Ultra Polyester-5	4.0
Disodium EDTA	0.1
Part C	
Preservative	q.s.
Part D	
Citric Acid, 20% in water	q.s.

¹Rockwood Additives, Southern Clay Products, Inc.

Part A

- Stir water rapidly while sprinkling in Laponite™ XLG.
- Mix until clear, 20 to 30 minutes.

Part B

- Combine water and glycerin.
- Heat while stirring until temperature reaches about 45°C.
- Add Eastman AQ™ 48 pellets and stir without further heating until dispersed.
- Add disodium EDTA and stir until dissolved.
- Cool to room temperature.

Slowly add Part B to Part A and mix until homogenous.

Part C

- Add Part C to combined Parts A and B and stir until thoroughly mixed.

Part D

- While stirring combined Parts A, B and C, slowly add citric acid to adjust pH to 4.2. (Note: pH will drift up to about 7.0 over 1 to 2 days.)

Directions for hair styling demonstration: Spray onto short, damp hair and arrange as desired.

The shear-thinning behavior of this spray-gel is apparent from the viscosity measured at various spindle speeds. (Brookfield LV spindle #4)

RPM	Approximate Viscosity (cP)
0.6	90,000
1.5	45,000
3.0	24,000
6.0	13,000
12.0	7,000

Eastman Chemical Company

Corporate Headquarters

P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.
Telephone:
U.S.A. and Canada, 800-EASTMAN
(800-327-8626)
Other Locations (1) 423-229-2000
Fax: (1) 423-229-1193
www.eastman.com

Eastman Chemical Latin America

9155 South Dadeland Blvd.
Suite 1116
Miami, FL 33156 U.S.A.
Telephone: (1) 305-671-2800
Fax: (1) 305-671-2805

Eastman Chemical B.V.

Fascinatio Boulevard 602-614
2909 VA Capelle aan den IJssel
The Netherlands
Telephone: (31) 10 2402 111
Fax: (31) 10 2402 100

Eastman Chemical Japan, Ltd.

AIG Aoyama Building 5F
2-11-16 Minami Aoyama
Minato-ku, Tokyo 107-0062 Japan
Telephone: (81) 3-3475-9510
Fax: (81) 3-3475-9515

Eastman Chemical Asia Pacific, Pte. Ltd.

#05-04 Winsland House
3 Killiney Road
Singapore 239519
Telephone: (65) 6831-3100
Fax: (65) 6732-4930

It is the responsibility of the cosmetic formulator or manufacturer to determine the suitability of all raw materials, including any Eastman product used in its final product in order to ensure safety and compliance with requirements of all appropriate U.S. and international regulatory agencies.

Material Safety Data Sheets providing safety precautions, that should be observed when handling and storing Eastman products, are available online or by request. You should obtain and review the available material safety information before handling any of these products. If any materials mentioned are not Eastman products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information, or of any product, method or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment and for the health and safety of your employees and purchasers of your products. NO WARRANTY IS MADE OF THE MERCHANTABILITY OR FITNESS OF ANY PRODUCT, AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Eastman and Eastman AQ are trademarks of Eastman Chemical Company.

© Eastman Chemical Company, 2009.