

EASTMAN

Eastman EastaPure™
electronic chemicals

DB solvent

Eastman EastaPure™ electronic chemicals

DB solvent

CAS: 112-34-5 (Diethylene glycol monobutyl ether)



Chemicals for the electronics industry

EastaPure™ DB solvent (diethylene glycol monobutyl ether) is the 7th product to be included in our current line of products. It is a high-boiling, slow-evaporating glycol ether providing low-trace metals content for sensitive electronic applications. High-purity specifications (low-trace metals) are required for solvents in semiconductor chip manufacturing, and special handling and storage procedures are used to maintain the high-purity specifications. Special analytical tests are used to measure critical trace metals in parts-per-billion levels (see Table 1).

Table 1: Special properties^a Upper limits for trace metals

Component	Upper Limit (parts/billion)	Component	Upper Limit (parts/billion)
Aluminum (Al)	100	Lithium (Li)	100
Barium (Ba)	100	Magnesium (Mg)	100
Cadmium (Cd)	100	Manganese (Mn)	100
Calcium (Ca)	100	Nickel (Ni)	100
Chromium (Cr)	100	Potassium (K)	100
Cobalt (Co)	100	Silver (Ag)	100
Copper (Cu)	100	Sodium (Na)	100
Gallium (Ga)	100	Strontium (Sr)	100
Germanium (Ge)	100	Titanium (Ti)	100
Iron (Fe)	100	Zinc (Zn)	100
Lead (Pb)	100		

^aListed in the Sales Specification.

Eastman EastaPure™ DB solvent is being presented for photoresist applications/formulations, specifically for photoresist removers/strippers. In addition to the special analytical results on some critical trace metals, Table 2 lists some typical properties and regulatory classifications for EastaPure™ DB solvent.

Table 2: Typical properties^a

Molecular weight	162.23
Empirical formula	C ₈ H ₁₈ O ₃
Color (Pt-Co scale), max.	10
Wt/vol @ 20°C, kg/L (lb/gal)	0.96 (7.94)
Solubility	
In water, @ 20°C	Complete
Water in, @ 20°C	Complete
Evaporation rate	
(n-Butyl acetate = 1)	0.003
(ether = 1)	4,034
Dilution ratio	
Toluene	3.9
VM&P Naphtha	1.9
Refractive index @ 20°C	1.4316
Vapor density (air = 1)	
@ 20°C	0.02 mm Hg
55°C	0.04 Kpa
Specific gravity @ 20/20°C	0.955
Boiling point @ 760 mm Hg, °C (°F)	230–235 (441–455)
Freezing point, °C (°F)	–76 (–105)
Flash point, Cleveland open cup, °C (°F)	111 (232)
Fire point, °C (°F)	117 (242)
Flammability limits in air, % by volume	
Lower @ 135°C	0.85
Upper @ 199°C	24.6
Autoignition temperature, °C (°F)	204 (400)
Hansen solubility parameters	
Nonpolar	7.8
Polar	3.4
Hydrogen bonding	5.2
Total	10.0
Surface tension @ 20°C, dynes/cm	30
Blush resistance @ 26.7°C (80°F)	85% RH
Electrical resistance, megohms	<0.3
Critical temperature, °C	380.8
Critical pressure, ATM	25.3
Critical volume, mL/g-mol	526
Expansion coefficient, per °C @ 20°C	0.00085
Heat of vaporization, cal/g-mol	12,920
Heat of combustion, kcal/g-mol	–1,109
Nitrocellulose solubility	Active
Maximum incremental reactivity (MIR)	2.7
Liquid viscosity @ 25°C, cP (mPa·s)	4.7
Liquid heat capacity @ 54°C, cal/g-mol	80.62

^aUnless noted otherwise, all tests are run at 23°C (73°F) and 50% relative humidity. Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.



**Eastman Chemical Company
Corporate Headquarters**

P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.

Telephone:
U.S.A. and Canada, 800-EASTMAN
(800-327-8626)
Other Locations, (1) 423-229-2000
Fax: (1) 423-229-1193

Eastman Chemical Latin America

9155 South Dadeland Blvd.
Suite 1116
Miami, FL 33156 U.S.A.

Telephone: (1) 305-671-2800
Fax: (1) 305-671-2805

Eastman Chemical B.V.

Fascinatio Boulevard 602-614
2909 VA Capelle aan den IJssel
The Netherlands

Telephone: (31) 10 2402 111
Fax: (31) 10 2402 100

**Eastman (Shanghai) Chemical
Commercial Company, Ltd. Jingan Branch**

1206, CITIC Square
No. 1168 Nanjing Road (W)
Shanghai 200041, P.R. China

Telephone: (86) 21 6120-8700
Fax: (86) 21 5213-5255

Eastman Chemical Japan, Ltd.

AIG Aoyama Building 5F
2-11-16 Minami Aoyama
Minato-ku, Tokyo 107-0062 Japan

Telephone: (81) 3-3475-9510
Fax: (81) 3-3475-9515

Eastman Chemical Asia Pacific Pte. Ltd.

#05-04 Winsland House
3 Killiney Road
Singapore 239519

Telephone: (65) 6831-3100
Fax: (65) 6732-4930

www.eastman.com

Material Safety Data Sheets providing safety precautions, that should be observed when handling and storing Eastman products, are available online or by request. You should obtain and review the available material safety information before handling any of these products. If any materials mentioned are not Eastman products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information, or of any product, method or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment and for the health and safety of your employees and purchasers of your products. NO WARRANTY IS MADE OF THE MERCHANTABILITY OR FITNESS OF ANY PRODUCT, AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

EastaPure and Eastman are trademarks of Eastman Chemical Company.

© Eastman Chemical Company, 2008.