

Eastman **SPECTAR**[™] FR1000 copolyester





Applications/uses Key attributes of Spectar sheet containing FR1000 concentrate Wall coverings Class A flammability rating (ASTM E84) thickness up to 60 mil in sheet form and 80 mil in profiles

- Corner guards
- Handrails
- Doorjambs

- Longevity of product life
- Chemical resistance
 - Stain resistance
 - Compliant with regulations restricting BPA, halogens, and certain heavy metals

Product description

Eastman Spectar™ FR1000 copolyester is a concentrate which can be added to Spectar and other Eastman copolyesters to produce extruded sheet and profiles which meet ASTM E-84 requirements for a Class A flammability rating for interior finish applications. These applications include wall protection panels, corner guards, and handrails typically installed in offices, hospitals, hotels, and schools.

Copolyester sheet containing Eastman Spectar FR1000 concentrate is tough, chemically resistant, odor free, and enables design freedom during fabrication. Its toughness enables the use of thinner gauge sheet than other common materials. It can also be extruded up to 12-mm (1/2-in.) thick and will not crystallize.

Fabrication ease

Copolyester sheet made with Eastman Spectar FR1000 concentrate can:

- Be laser cut, routed, drilled, or die punched
- Be bent hot or cold
- Be joined with screws, rivets, bolts, or solvent welded
- Be cut with conventional table, band, or radial arm saws with blades commonly used for plastic
- Produce finished edges easily by polishing with commercial edge-finishing equipment, sanding, solvents, flame polishing, or buffing
- Form strong bonds with commercially available cements and solvents
- Easily accept screen printing, painting, and hot stamping

EASTMAN

Eastman Chemical Company Corporate Headquarters

P.O. Box 431 Kingsport, TN 37662-5280 U.S.A.

Telephone: U.S.A. and Canada, 800-EASTMAN (800-327-8626) Other Locations, (1) 423-229-2000 Fax: (1) 423-229-1193

Eastman Chemical Latin America

9155 South Dadeland Blvd. Suite 1116 Miami, FL 33156 U.S.A.

Telephone: (1) 305-671-2800 Fax: (1) 305-671-2805

Eastman Chemical B.V.

Fascinatio Boulevard 602-614 2909 VA Capelle aan den IJssel The Netherlands

Telephone: (31) 10 2402 111 Fax: (31) 10 2402 100

Eastman (Shanghai) Chemical Commercial Company, Ltd. Jingan Branch

1206, CITIC Square No. 1168 Nanjing Road (W) Shanghai 200041, P.R. China

Telephone: (86) 21 6120-8700 Fax: (86) 21 5213-5255

Eastman Chemical Japan Ltd.

MetLife Aoyama Building 5F 2-11-16 Minami Aoyama Minato-ku, Tokyo 107-0062 Japan

Telephone: (81) 3-3475-9510 Fax: (81) 3-3475-9515

Eastman Chemical Asia Pacific Pte. Ltd.

#05-04 Winsland House 3 Killiney Road Singapore 239519

Telephone: (65) 6831-3100 Fax: (65) 6732-4930

www.eastman.com

For more information, call 1-800-Eastman, visit www.Eastman.com\FR1000, or email ryoung@eastman.com.

Material Safety Data Sheets providing safety precautions that should be observed when handling and storing Eastman products are available online or by request. You should obtain and review the available material safety information before handling any of these products. If any materials mentioned are not Eastman products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. NO WARRANTY IS MADE OF THE MERCHANTABILITY OR FITNESS OF ANY PRODUCT, AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Eastman and Spectar are trademarks of Eastman Chemical Company.

© Eastman Chemical Company, 2012.