

The very best color

Eastman cellulose acetate

Long the industry standard, Eastman cellulosic acetate flake and granules help you create frames with the sharp, deep, and rich color effects that distinguish truly premium glasses from everything else. The outstanding clarity offered by Eastman cellulosic acetate produces frames with the vibrant and intense visual effects that denote the very best in craftsmanship and quality.

Great versatility

Eastman now offers a range of cellulosic acetate flake grades that can be used, with equal effectiveness, for both extrusion and dry block processes. There's no longer a need to source different raw materials and manage the complexity of different SKUs for different manufacturing approaches.

Fit for purpose

There's no substitute for great color. But different designs and color effects have different requirements for clarity and colorability. Eastman's range of cellulosic acetate grades allows you to match your raw material needs and your aesthetic requirements at a price point consistent with the specifications.

Consistency and quality

Scrap is a huge challenge in the eyewear industry. The consistency and quality of Eastman products—along with our world-class technical support—can help you reduce defects and achieve better economics.

No one knows cellulose acetate better than Eastman—the world's leading supplier of cellulose acetate flake for extrusion, wet, and dry block processes.

Eastman polymer solutions for eyewear

Cellulosic acetate | Copolyesters | CAP | Bioplastics

MANUFACTURING	BENEFITS	EASTMAN ADDED VALUE
Dry block Extrusion Wet block Injection molding	Excellent clarity and colorability Outstanding comfort and feel Great chemical resistance	Diverse portfolio World-class technology Global technical support History of innovation and product development 100 years of commitment





Eastman Corporate Headquarters
P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626)
Other Locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company ("Eastman") and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2020 Eastman. Eastman brands referenced herein are trademarks of Eastman or one of its subsidiaries or are being used under license. The ® symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.