

# Eastman's specialty alkyl alkanolamines (AAAs) and alkyl hydroxylamines

## Adding value to diverse applications and markets

Formulators and others looking for high-quality amines and amine derivatives can turn to Eastman's range of specialty alkyl alkanolamines and alkyl hydroxylamines. You can rely on our experience and expertise to provide you with the best solution to meet your needs.

With plants in the United States, China, and Belgium, Eastman is the world's largest producer of basic alkyl alkanolamines like DMAE and MDEA. We also make a series of useful short-chain specialty alkanolamines (amino alcohols).

These amino alcohols have interesting physical properties and structures and serve as raw materials and additives in a wide variety of markets including pharmaceuticals, water treatment, hydraulic fluids, metalworking fluids, coatings, and inks. For example, EAE is used as a solvent in carbon capture (CCS) as well as an intermediate for hydroxychloroquine—a common drug for malaria and other diseases. DEAE, morpholine, and cyclohexylamine are the three most common amines used in boiler water treatment to prevent corrosion. IPAE and BAE are commonly used in industrial lubricants such as metalworking fluids or water-based hydraulic fluids. Our newest amine, MDIPA, is used to make fabric softeners and other surfactants.

### DEHA

Eastman has made DEHA in the U.S. for almost 50 years and remains the world's largest producer—and the only producer in the Americas. DEHA is a very powerful oxygen and free radical scavenger used in boiler water treatment, polymer production, and photographic chemicals as a color stabilizer for various products. It is also used in other markets and applications.

## Specialty alkyl alkanolamines (AAA)

### Products

#### Ethyls

- Ethylaminoethanol (EAE)
- Ethyldiethanolamine (EDEA)\*
- Diethylaminoethanol (DEAE)

#### Propyls

- Isopropylaminoethanol (IPAE, mixed isomers)
- Diisopropylaminoethanol (DIPAE)\*

#### Butyls

- *n*-Butylaminoethanol (BAE)
- *t*-Butylaminoethanol (TBAE)
- *t*-Butyldiethanolamine (TBDEA)\*
- *n*-Butyldiethanolamine (BDEA)
- Di-*n*-butylaminoethanol (DBAE)












#### Alkyl propanols

- Dimethylamino-2-propanol (DMA 2P, anhydrous)
- Dimethylamino-2-propanol (DMA 2P, 77% aqueous)
- Methyl-diisopropanolamine (MDIPA)

\*Can be produced based on significant customer need. Contact us to discuss these or other AAAs (e.g., CS+).

### Applications

- Metalworking fluids
- Coatings/inks
- Photographic chemicals
- Acrylic monomers
- Gas treatment
- Boiler water treatment
- Industrial lubricants like hydraulic fluids
- Fabric softeners, car wash cleaners, and other surfactant applications
- Electronics

Ethylaminoethanol (EAE)	
Diethylaminoethanol (DEAE)	
Isopropylaminoethanol (IPAE, mixed isomers)	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">             Isopropylaminoethanol (70%)         </div> <div style="text-align: center;">             Isopropylaminodiethanol (30%)         </div> </div>
Diisopropylaminoethanol (DIPAE)*	
<i>n</i> -Butylaminoethanol (BAE)	
<i>t</i> -Butylaminoethanol (TBAE)	
<i>n</i> -Butyldiethanolamine (BDEA)	
Di- <i>n</i> -butylaminoethanol (DBAE)	
Dimethylamino-2-propanol (DMA2P, anhydrous)	
Methyldiisopropanolamine (MDIPA)	



## Physical properties

Product	Formula (commercial specification)	CAS	GMW	Density (22°C), g/mL	pKa <sup>a</sup>	Flash point, °F (°C)	Solubility in water	Vapor pressure, mm Hg	Boiling point, °C
Diethylaminoethanol (DEAE)	(Et) <sub>2</sub> NCH <sub>2</sub> CH <sub>2</sub> OH (99.6%)	100-37-8	117.2	0.882	9.95	125 <sup>b</sup> (52)	Miscible	1.4	161
Diisopropylaminoethanol (DIPAE)	(iPr) <sub>2</sub> NCH <sub>2</sub> CH <sub>2</sub> OH (99%)	96-80-0	145.2	0.873	10.13	153 <sup>c</sup> (67)	9.2%	<1	188–192 (commercial)
Ethylaminoethanol (EAE)	EtNHCH <sub>2</sub> CH <sub>2</sub> OH (98%)	110-73-6	89.1	0.916	10.07	159 <sup>c</sup> (70)	Miscible	<1	170
Dimethylamino-2-propanol (DMA 2P)	(Me) <sub>2</sub> NCH <sub>2</sub> CHOHCH <sub>3</sub> (99%)	108-16-7	103.2	0.851	9.53	82 <sup>b</sup> (28)	Miscible	20	121–127 (commercial)
Dimethylamino-2-propanol 77% (DMA 2P 77% mixed)	(Me) <sub>2</sub> NCH <sub>2</sub> CHOHCH <sub>3</sub> (76%–78%, aqueous)	108-16-7	103.2	0.914	9.53	99 <sup>b</sup> (37)	Miscible	20	96 (azeotrope)
Di- <i>n</i> -butylaminoethanol (DBAE)	(Bu) <sub>2</sub> NCH <sub>2</sub> CH <sub>2</sub> OH (99%)	102-81-8	173.3	0.858	9.95	201 <sup>c</sup> (94)	0.4%	<0.1	230
Isopropylaminoethanol, mixed (IPAE mixed) <sup>d</sup>	iPrNHCH <sub>2</sub> CH <sub>2</sub> OH (70%) iPrN(CH <sub>2</sub> CH <sub>2</sub> OH) <sub>2</sub> (30%) (99%)	109-56-8 121-93-7	103.2 147.2	0.929	9.88	168 <sup>c</sup> (75)	Miscible	2	110–265 (commercial)
<i>n</i> -Butylaminoethanol (BAE)	BuNHCH <sub>2</sub> CH <sub>2</sub> OH (99%)	111-75-1	117.2	0.892	10.03	205 <sup>c</sup> (96)	Miscible	<0.1	199
<i>n</i> -Butyldiethanolamine (BDEA)	BuN(CH <sub>2</sub> CH <sub>2</sub> OH) <sub>2</sub> (99%)	102-79-4	161.3	0.968	8.91	286 <sup>b</sup> (141)	Miscible	<<0.01	274 (741 mm Hg)
<i>t</i> -Butylaminoethanol (TBAE)	tBuNHCH <sub>2</sub> CH <sub>2</sub> OH (99%)	4620-70-6	117.2	0.869	10.24	156 <sup>c</sup> (69)	Miscible	<1	175 (mp = 43°C)
Methyldiisopropanolamine (MDIPA)	MeN(CH <sub>2</sub> CHOHCH <sub>3</sub> ) <sub>2</sub> (90%) MeN(CH <sub>2</sub> CHOHCH <sub>3</sub> )(CHCH <sub>3</sub> CH <sub>2</sub> OH) (10%) (98%)	4402-30-6 85154-18-3	147.2	0.958	8.88 <sup>e</sup>	241 <sup>c</sup> (116)	Miscible	0.04 <sup>f</sup>	226

<sup>1</sup>Measurements refer to the protonated amine at 25°C in aqueous solution.

<sup>2</sup>Flash points were determined by the TAG closed cup method.

<sup>3</sup>Flash points were determined by the Pensky-Martens closed cup method.

<sup>4</sup>This product is a mixture of 70% wt/wt *n*-alkylmonoethanolamine and 30% wt/wt *n*-alkyldiethanolamine. The material has an average GMW of 114.5–117.5 (a.k.a. combining weight).

<sup>5</sup>SciFinder (predicted): most basic at 25°C

<sup>6</sup>SciFinder (predicted): at 25°C



# DEHA

## Products


### Ethyls

- Diethylhydroxylamine (DEHA, 85% aqueous)
- Diethylhydroxylamine (DEHA, anhydrous)
- Term-N-ator™ P (branded; FDA-approved for food contact and patented DEHA for PVC short stopper use only in the Americas)

## Applications

- Boiler water treatment
- SBR/PVC production
- Oil-field chemicals
- Chemical processing
- Photographic chemicals
- Radical scavenging
- Color inhibition

Diethylhydroxylamine (DEHA)



## Physical properties

Product	Formula (commercial specification)	CAS	GMW	Density (22°C)	pKa* (22°C)	Appearance	Flash point, <sup>b</sup> °F (°C)	Solubility in water (20°C)	Vapor pressure (25°C), mm Hg	Boiling point (pure material) (760 mm Hg), <sup>b</sup> °C
DEHA, 85% solution	(Et)2NOH (85%, aqueous)	3710-84-7	89.1	0.898	5.61	Clear to light yellow liquid	115 (46)	35	32	125–130 with decomposition
DEHA anhydrous	(Et)2NOH (98%)	3710-84-7	89.1	0.870	5.61	Clear to light yellow liquid	122 (50)	35	5	133 with decomposition

\*This value was generated by an ACD calculation.

<sup>b</sup>Flash points were determined by the TAG closed cup method.

**EASTMAN**  
The results of insight™

Eastman Corporate Headquarters  
P.O. Box 431  
Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626)  
Other Locations, +(1) 423-229-2000

[www.eastman.com/locations](http://www.eastman.com/locations)

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company ("Eastman") and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2020 Eastman. Eastman brands referenced herein are trademarks of Eastman or one of its subsidiaries or are being used under license. The ® symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.