

Eastman Embrace[™] HY copolyester

High-yield shrink film and labels for packaging

Eastman Embrace[™] HY copolyester is another member of the innovative Embrace family of resins used in labeling and packaging. This product provides smarter solutions for the shrink label market.

Material attributes

Sustainable packaging innovation

- Shrink labels can be made with up to 8% renewable content.*
- ~30% lower density than other copolyesters
- Low density means less material for the same label.

Superior aesthetics

- Printable—delivers 360° container graphics (for billboard effect)
- Naturally white-eliminates need for printed white flood coats or pigmented bottle
- Soft touch—organic feel and slip resistant
- Noise-free film for squeezable packaging

Improved functionality

- UV and visible light-blocking capability—less ink to block more light
- Excellent for dairy, juices, wine, and vitamin products that require light blocking
- Forms around highly contoured or complex containers (up to 70% ultimate shrinkage)
- MD growth—eliminates "smiley faces"
- · Lower shrink force—great for use on thin-walled plastic containers
- Perforation capabilities—supports tamper evidence

Sleeved by Rivièra Product Decorations

*Based on extruders adding 25% Eastman Embrace HY additive; actual percentage may vary according to extruder formulation.

To learn more about this product and packaging innovation, visit us at www.eastman.com/EmbraceHY or email us at embrace@eastman.com.

The results of **insight**™

Embrace light-blocking comparison chart



Based on extruders adding 25% Embrace HY; actual percentage may vary according to extruder formulation.

This product is created by combining Embrace LV with Embrace HY, and through the extrusion process, this composition creates a white, opaque microvoided shrink film.



Eastman Corporate Headquarters P.O. Box 431 Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626) Other Locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company ("Eastman") and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2018 Eastman. Eastman brands referenced herein are trademarks of Eastman or one of its subsidiaries or are being used under license. The © symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.