

Parallel systems, contrasting results

Therminol® 66 heat transfer fluid delivers excellent performance for Grupo Primex.

Reliable heat transfer fluids are vital to the ability of manufacturers to operate efficiently and productively. However, some heat transfer fluids can degrade over time, resulting in deteriorating performance and impacting operating costs and product quality. With these possible consequences, how can manufacturers ensure they are choosing the right heat transfer fluid and prevent these problems from occurring?

Grupo Primex (now known as Mexichem)—Latin America's largest manufacturer of PVC resins, phthalic anhydride, plasticizers, and PVC compounds—operates two parallel heat transfer systems that present a unique comparison. Therminol® 66 heat transfer fluid has supported one of these systems for more than 15 years. A diaryl alkyl chemistry product, rated to 350°C (660°F), has been utilized in the second system for five years.

Contrasting results

Since the 1980s, the system supported by Therminol 66 has performed with excellent results when compared to the alternative fluid in a separate heat transfer system.

Francisco Nava, production manager for Grupo Primex at the time of the study, describes the performance concerns of the alternative fluid heat transfer process. "We were experiencing losses in distillation efficiency, increases in system vapor pressures, increased unplanned downtime, and impacts to our finished product quality."

The decision to change

Grupo Primex turned to the Therminol technical support team for a complimentary fluid analysis that is a part of the TLC Total Lifecycle Care® program. According to the analysis completed by the technical

"... customer service—such as that provided by the TLC Total Lifecycle Care program—is invaluable."

Francisco Nava, production manager, Grupo Primex

team, the Therminol fluid composition demonstrated greater resistance to chemical changes of concern under the operating conditions of the process, sustaining excellent performance over a longer time period.

"Our system utilizing Therminol 66 heat transfer fluid was operating smoothly. The decision to switch to Therminol 66 in the other system was clear," said Nava.

The transition to Therminol 66 was made in June 2005. Additionally, Therminol FF flushing fluid would be utilized to clean Grupo Primex's second system of the alternative fluid.

Expected results

According to Nava, "In the 15 years that we have operated our system using Therminol 66 heat transfer fluid, we have never experienced downtime or other problems. Cleaning our other system with Therminol FF and switching to Therminol 66 yielded the same consistent, outstanding results for both systems."

Mr. Nava's advice to other manufacturers when choosing a heat transfer fluid: "In addition to looking at the efficiency and life span of the heat transfer fluid, our experience demonstrates that customer service—such as that provided by the TLC Total Lifecycle Care program—is invaluable."

For more information, or to find the sales or technical contact nearest you, visit the "Contact us" page on our website:
www.therminol.com.

North America
Solutia Inc.
A subsidiary of Eastman Chemical Company
575 Maryville Centre Drive
St. Louis, MO 63141 U.S.A.
Telephone:
Customer Service, 800-426-2463
Technical Service, 800-433-6997
Fax: Customer Service, (1) 314-674-7433

Latin America
Solutia Brasil Ltda.
A subsidiary of Eastman Chemical Company
Rua Alexandre Dumas, 1711—Birmann 12—
7º Andar 04717-004
São Paulo, SP, Brazil
Telephone:
Brazil, 0800 55 9989
Other Locations, +55 11 3579 1800
Fax: +55 11 3579 1833

Europe/Middle East/Africa
Solutia Europe SPRL/BVBA
A subsidiary of Eastman Chemical Company
Corporate Village—Aramis Building
Leonardo Da Vincilaan 1
1935 Zaventem, Belgium
Telephone: +32 2 746 5000
Fax: +32 2 746 5700

Asia Pacific
Eastman (Shanghai) Chemical
Commercial Company Ltd.
Building 3, Yaxin Science & Technology Park
Lane 399 Shengxia Road
Pudong New District
201210, Shanghai, P.R. China
Telephone: +86 21 6120 8700
Fax: +86 21 5027 9229

EASTMAN
The results of insight™

Eastman Chemical Company
Corporate Headquarters
P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.
U.S.A. and Canada, 800-EASTMAN (800-327-8626)
Other Locations, +(1) 423-229-2000
www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2015 Eastman Chemical Company. Eastman brands referenced herein are trademarks of Eastman Chemical Company or one of its subsidiaries. The ® used on Eastman brands denotes registered trademark status in the U.S.; marks may also be registered internationally. Other companies' brands referenced herein are trademarks of their respective owners.