

Eastman Tritan™ copolyester—a new option for clear electronic device applications

Eastman Tritan™ copolyester

- Tritan is an innovative, new-generation copolyester that retains the versatility of traditional copolyesters while offering higher temperature performance and impact resistance. The unique properties of Tritan deliver advantages over other clear thermoplastics.
- Functional attributes of Eastman Tritan™ copolyester:
 - Toughness
 - Clarity
 - Excellent chemical resistance
 - Higher temperature performance compared to traditional copolyester
 - Lower melt processing temperature compared to standard polycarbonate
 - Good adhesion to ink/films
 - Low levels of residual stress
 - Can be a drop-in replacement for PC, PMMA, and PC/polyester with minor or no modifications



Striking a balance

- Tritan offers good clarity, toughness, chemical resistance, and flow but with melt temperature sufficiently cool enough to avoid ink washout. Tritan offers this at a cost generally lower than some blended material options.
- Tritan boasts inherently low levels of residual stress which suggests it's well-suited for complex designs and shapes.
- Tritan is suitable for IMD and may be an attractive option for thin-wall lenses in mobile phones, appliances, and medical devices.

Material	Impact resistance, notched Izod (J/m) ^a	Light transmission (%) ^b	Haze ^b	Melt processing temperature (°C)
Tritan copolyester —VX351HF	980	91	<1%	260–280

^aASTM D256 @ 23°C

^bASTM D1003



The results of insight™

**Eastman Chemical Company
Corporate Headquarters**

P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.

Telephone:
U.S.A. and Canada, 800-EASTMAN (800-327-8626)
Other Locations, (1) 423-229-2000
Fax: (1) 423-229-1193

Eastman Chemical Latin America

9155 South Dadeland Blvd.
Suite 1116
Miami, FL 33156 U.S.A.

Telephone: (1) 305-671-2800
Fax: (1) 305-671-2805

Eastman Chemical B.V.

Fascinatio Boulevard 602-614
2909 VA Capelle aan den IJssel
The Netherlands

Telephone: (31) 10 2402 111
Fax: (31) 10 2402 100

**Eastman (Shanghai) Chemical
Commercial Company, Ltd. Jingan Branch**

1206, CITIC Square
No. 1168 Nanjing Road (W)
Shanghai 200041, P.R. China

Telephone: (86) 21 6120-8700
Fax: (86) 21 5213-5255

Eastman Chemical Japan Ltd.

MetLife Aoyama Building 5F
2-11-16 Minami Aoyama
Minato-ku, Tokyo 107-0062 Japan

Telephone: (81) 3-3475-9510
Fax: (81) 3-3475-9515

Eastman Chemical Asia Pacific Pte. Ltd.

#05-04 Winsland House
3 Killiney Road
Singapore 239519

Telephone: (65) 6831-3100
Fax: (65) 6732-4930

www.eastman.com

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company makes no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of their suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2013 Eastman Chemical Company. Eastman, The results of insight, and Tritan are trademarks of Eastman Chemical Company.