SALES SPECIFICATIONS

Sales Specification No : 418-16 Effective Date : 10/15/2012

Page No. 1 of 1



PRODUCT NAME

Eastman(TM) Triethyl Phosphate

SPECIFICATIONS		
PROPERTY	LIMITS	TEST METHOD
Appearance	Clear and Free of Suspended Matter	TCMD-A-AN-G-MIS-20
Acid as Phosphoric, %	0.02 MAX	TCMD-A-AN-G-VA-391
Water, %	0.0500 MAX	TCMD-A-AN-G-VA-336
Chlorides, ppm	1 MAX	TCMD-A-AN-G-TBA-24
Sulfates, ppm	5 MAX	TCMD-A-AN-418-TBA-65
Visual Color, pcs	10 MAX	TCMD-A-AN-G-VCC-11
Alcohol Content, ppm	100 MAX	TCMD-A-AN-G-GC-267
Triethyl Phosphate, %	99.85 MIN	TCMD-A-AN-G-GC-267
Specific Gravity @ 20/20°C	1.070 - 1.072	TCMD-A-AN-G-DEN-2
Refractive Index @ 25C	1.401 - 1.405	TCMD-A-AN-G-RI-3

 $\textbf{Eastman Chemical Company} \cdot \textbf{P.O. BOX 511} \cdot \textbf{Kingsport}, \textbf{Tennessee 37662 USA} \cdot \textbf{1-800-EASTMAN} \cdot \textbf{1-423-229-2000} \cdot \textbf{www.EASTMAN}. \textbf{company} \cdot \textbf{Notes of the property of the pr$

Sales Specification available on Eastman.com

For reasons of safety and accuracy, the person performing this procedure must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers. Limits in this specification are applicable only to data obtained by the referenced test method.

Neither Eastman Chemical Company nor its marketing affliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the seller's conditions of sale.