SALES SPECIFICATIONS

Sales Specification No: 9051-6 Effective Date: 08/31/2007

Page No. 1 of 1



PRODUCT NAME

Eastman(TM) Methyl Acetate

SPECIFICATIONS		
PROPERTY	LIMITS	TEST METHOD
Appearance	Clear and Free of Suspended Matter	TCMD-A-AN-G-MIS-20
Non-volatile Matter, g/100mL	0.005 MAX	TCMD-A-AN-G-GA-6
Acetone, %	0.02 MAX	TCMD-A-AN-G-GC-382
Acid as Acetic, %	0.1500 MAX	TCMD-A-AN-G-VA-352
Other Impurities, %	0.20 MAX	TCMD-A-AN-G-GC-382
Methanol, %	2.50 MAX	TCMD-A-AN-G-GC-382
Visual Color, pcs	5 MAX	TCMD-A-AN-G-VCC-11
Heavy Metals as Lead, ppm	10.0 MAX	TEAD-A-AN-G-ICP-105
Methyl Acetate, %	96.00 MIN	TCMD-A-AN-G-GC-382
Specific Gravity @ 20/20°C	0.930 - 0.950	TCMD-A-AN-G-DEN-2
Water, %	1.5000 MAX	TCMD-A-AN-G-VA-307

 $\textbf{Eastman Chemical Company} \cdot \textbf{P.O. BOX 511} \cdot \textbf{Kingsport}, \textbf{Tennessee 37662 USA} \cdot \textbf{1-800-EASTMAN} \cdot \textbf{1-423-229-2000} \cdot \textbf{www.EASTMAN}. \textbf{company} \cdot \textbf{Co$

Sales Specification available on Eastman.com

For reasons of safety and accuracy, the person performing this procedure must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers. Limits in this specification are applicable only to data obtained by the referenced test method.

Neither Eastman Chemical Company nor its marketing affliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the seller's conditions of sale.