

SALES SPECIFICATIONS

Sales Specification No : 10104-8

Effective Date : 03/01/2023

Page No. 1 of 1

EASTMAN**PRODUCT NAME****Eastman AQ(TM) 38S Polymer****SPECIFICATIONS**

PROPERTY	LIMITS	TEST METHOD
Inherent Viscosity	0.32 - 0.40	EMN-A-AC-G-V-1
Color: CIE b*	7.0 - 19.7	EMN-A-AC-G-RS-1
Appearance	Pale Amber Pellets	VISUAL INSPECTION

Glass Transition(Tg) Temperature (2nd Cycle) (TEPO-A-AN-G-DTP-5-S10) - No sales specification limits apply to this property; however, analytical results will be provided to customers upon request.

Eastman AQ 38S is hygroscopic. If exposed to excess moisture, clumping is likely to occur. Eastman AQ 38S when stored in the original unopened container, in an enclosed area, protected from moisture, high temperatures and contamination, this product is estimated to continue to meet applicable sales specification. Please reference SDS for correct storage temperatures.

Eastman Chemical Company · P.O. BOX 511 · Kingsport, Tennessee 37662 USA · 1-800-EASTMAN · 1-423-229-2000 · www.EASTMAN.com

Sales Specification available on Eastman.com

For reasons of safety and accuracy, the person performing this procedure must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers. Limits in this specification are applicable only to data obtained by the referenced test method.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the seller's conditions of sale.