

SALES SPECIFICATION

EASTMAN

Specification No: 34058-1 and 34088-1

Effective Date: 01 April 2013

Page 1 of 1

PRODUCT NAME

Santoflex™ 6PPD Liquid

SPECIFICATIONS

PROPERTY	LIMITS	TEST METHOD
Appearance	Purple brown liquid	FF97.5
Purity (GC), %	95.0 Minimum	FGC97.10
Heat Loss, %	0.5 Maximum	FGr97.7
Ash, %	0.1 Maximum	FGr90.9

Note: Appearance applies to product in liquid form above the typical melt point of 46 to 51°C. Material solidifies below this point.

Eastman™ and Santoflex™ are trademarks of Eastman Chemical Company.

Eastman Chemical Company · P.O. Box 511 · Kingsport, Tennessee 37662 USA · 1-800-EASTMAN · 1-423-229-2000 · www.EASTMAN.com

For reasons of safety and accuracy, the person performing this procedure must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers. Limits in this specification are applicable only to data obtained by the referenced test method.

Neither Eastman Chemical Company nor its marketing affiliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product; and nothing herein waives any of the seller's conditions of sale.