

Waterproof mascara with Eastman AQ™ 55S polymer

Part	Ingredient	Wt%	Quantity (grams)	INCI	Manufacturer
A	Deionized water	48.65	38.92	Water (aqua)	—
	Solagum™ AX	2.50	2.00	Acacia senegal gum (and) xanthan gum	SEPPIC
	Triethanolamine 90% Care	0.50	0.40	Triethanolamine	BASF
	Provitamin B5 powder	0.10	0.08	DL-panthenol	DSM
B	AQ 55S (solution 30%)	15.00	12.00	Polyester-5	Eastman
C	Beeswax	7.50	6.00	Beeswax (cera alba)	Strahl & Pitsch
	Carnauba wax	2.10	1.68	Carnauba wax	Strahl & Pitsch
	Microcrystalline wax pastille SP-16	3.00	2.40	Microcrystalline wax	Strahl & Pitsch
	Stearic acid USP (triple pressed)	5.00	4.00	Stearic acid	JEEN
	Foralyn™ 5020-F CG	1.50	1.20	Hydrogenated rosin ester	Synthomer
	Vitamin E	0.10	0.08	DL- <i>alpha</i> -tocopherol	DSM
	Crodamol™ GTCC	2.00	1.60	Caprylic/capric triglyceride	Croda
	Eutanol® G	1.50	1.20	Octyldodecanol	BASF
	XIAMETER™ PMX-200 Fluid	1.50	1.20	Dimethicone	Dow
D	Black iron oxide	8.00	6.40	CI 77499	—
E	Mineral base	0.25	0.20	Mica (and) zinc oxide (and) titanium	—
	KEM CP	0.80	0.64	Phenoxyethanol (and) chlorphenesin	Akema

Continued >>>

Procedure

1. Weigh out part A into a clean, sanitized, stainless steel mixing vessel with mixer/homogenizer attachment, and heat it between 70° and 75°C. Incorporate Solagum at medium speed (500 rpm).
2. Weigh out part C heated to 70°–75°C and add to part A while mixing until parts A and C are homogeneous. (mix speed 800–1,000 rpm).
3. Once parts A and C are homogeneous, incorporate part B. Mix until homogeneous.
4. Stop heat and incorporate part D into parts A, B, and C (increase mix speed to 1,800–2,000 rpm). Mix until pigment is homogeneously dispersed.
5. Start cooling down. Incorporate part E at less than 50°C.
6. Adjust pH if required



Eastman Corporate Headquarters
P.O. Box 431
Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626)
Other locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company ("Eastman") and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2022 Eastman. Eastman brands referenced herein are trademarks of Eastman or one of its subsidiaries or are being used under license. The ® symbol denotes registered trademark status in the U.S.; marks may also be registered internationally. Non-Eastman brands referenced herein are trademarks of their respective owners.